

## Super Heavy Duty Diesel Coolant Premix (HDDCTU)

FIRST CHOICE, RIGHT CHOICE, EVERYTIME.

Nulon Super Heavy Duty Diesel Coolant Premix is specifically formulated to meet the modern technology requirements of all diesel passenger cars, SUV, 4x4, Light Commercial and Heavy Duty diesel vehicles. Guaranteed to protect for 8 Years or 1.2 million kilometres or 12,000 hours.

### Benefits

- Guaranteed to protect for 8 years or 1.2 million kilometres or 12,000 hours
- Suitable for every diesel passenger car, SUV, 4x4, light commercial and heavy duty vehicle
- Use as an OEM replacement coolant
- Provides maximum anti-freeze/anti-boil protection
- Ensures total anti-corrosion protection for the entire cooling system
- No Supplemental Coolant Additive (SCA's) top-up required during life of coolant
- Exceeds Australian AS 2108-2004 Type A standard, plus international and national vehicle industry standards (see below)



### Directions for use

#### DIRECTIONS AS TOP UP

Add as top-up to existing coolant, then start the engine and turn the heater on. When the engine is warm, turn it off and allow it to cool. Check the coolant level, and top it up if necessary.

#### WARNING:

Never mix coolants from different manufacturers. DO NOT mix Nulon HD Diesel Coolant with green, red or blue coolant.

### Safety Directions

**SAFETY:** Harmful if swallowed. May cause respiratory irritation. Use only outdoors or in a well-ventilated area. Store locked up.

**FIRST AID: IF SWALLOWED:** Immediately call a POISON CENTRE or doctor/physician. Rinse mouth. **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor (at once).

**ENVIRONMENT:** Avoid release to the environment. Dispose of contents/container in accordance with local council regulations.

Meets or exceeds the following oil industry specifications	
AS Claims	AS 2108-2004 Type A
ASTM	ASTM D1384, ASTM D2570, ASTM D2809, ASTM D3306, ASTM D4340, ASTM D4985, ASTM D6210
Other Claims	JIS K2234 (Japan), TMC RP 329
Society of Automotive Engineers	SAE J1034, SAE J1941

### Pack Sizes



Part No: HDDCTU-1  
1 Litre - 6 Per Carton  
Barcode: 9311090 004832



Part No: HDDCTU-5  
5 litres - 3 Per Carton  
Barcode: 9311090006287