

Full Synthetic Multi-Vehicle Power Steering Fluid (PSFMV)

Nulon Full Synthetic Multi-Vehicle Power Steering Fluid (PSFMV) is an advanced fluid that suits the power steering system requirements of the vast majority of Australian, Japanese, Korean, American and European vehicles. It contains a superior anti-wear and detergency formulation over that of regular power steering fluids.

Benefits

- 100% synthetic formulation
- Suitable for most power steering systems
- Reduces steering vibration & chatter/shudder
- Extends power steering system durability
- Red liquid to mix with existing fluid when used as a top-up



Directions for Use

With the engine off, fill power steering fluid reservoir to the specified level. Follow directions in owner's manual for adding fluid. Do not overfill.

Specifications

Suitable for the following specifications:

- CHRYSLER MS-1872
- CHRYSLER MS-5931, P/N 04883077
- CHRYSLER MS-9602, ATF+4
- FORD M2C195-A
- GM P/N 89021184
- GM 9985010, P/N 1052884
- GM 9985835, P/N 12345866
- HYUNDAI PSF-3
- KIA PSF-3
- MERCEDES BENZ 236.3, P/N 000 989 88 03
- MITSUBISHI PS FLUID
- MITSUBISHI DIAMOND SP III
- NISSAN PSF-II I
- SAAB P/N (45) 30 09 800
- SUBARU P/N K0209A0080
- TOYOTA PSF TYPE EH, P/N 008886-01

Safety

Avoid contact with skin and eyes. If contact occurs, wash thoroughly with soap and water. After use, dispose of container in a responsible manner. Do not reuse container for any other purpose. For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor (at once). ENVIRONMENT: Do not pollute drains, soil or water with used products. After use, dispose of container in a responsible manner. Do not dispose of to landfill. Disposal of container should comply with local council regulations.

Typical Properties

Physical Properties	Typical Values
Kinematic Viscosity @100°C, cSt	7.190
Kinematic Viscosity @40°C, cSt	29.73
Viscosity Index, ASTM D2270	220
Density @15°C, ASTM D4052, kg/L	0.8372
Flash Point, °C, ASTM D92	225
Pour point, °C, ASTM D97	-45
Phosphorus content, ppm	248

Pack Sizes



Part No: PSFMV
 500mL - 6 Per Carton
 Barcode: 9311090002463
 Material No: 602278463