

## Power Steering Stop Leak and Conditioner (G65)

Nulon Power Steering Stop Leak & Conditioner uses the latest seal rejuvenating and high performance anti-wear additives, including PTFE. It reduces and prevents messy oil leaks and premature wear to extend power steering component life. Compatible with most types of power steering fluid.

### Benefits

- Reduces noise & steering chatter/shudder
- Reduces leaks fast
- Helps prevent seal damage & wear
- Extends power steering component life
- Rejuvenates worn & hardened seals



### Directions for use

Add to power steering reservoir. Use 1 bottle for every 1.5 litres of power steering fluid. It may be necessary to drain fluid out of the power steering reservoir to enable the full contents of this bottle to be added.

NOTE: It may take up to 14 days or 500 km to achieve maximum benefits.

### First aid

For advice, contact a Poisons Information Centre (Phone e.g. Australia 131 126; New Zealand 0800 764 766) or a doctor (at once).

### Typical Properties

| Tests                     | ASTM   | Nulon G65 |
|---------------------------|--------|-----------|
| Colour                    | Visual | Red       |
| Flash point, COC, °C      | D92    | 134       |
| Foam characteristics      | D892   | Nil foam  |
| Viscosity @ 40°C, cSt     | D445   | 47.42     |
| Viscosity @ 100°C, cSt    | D445   | 8.540     |
| Viscosity index           | D2270  | 159       |
| Density, Kg/L             | D1298  | 0.8842    |
| Pour point, °C            | D97    | -45       |
| Melting point of PTFE, °C | D1457  | >325      |

### Pack Sizes



Part No: G65  
300 ml - 6 Per Carton  
Barcode: 9311090000360