

Semi Synthetic 75W-80 Smooth Shift Manual Gearbox and Transaxle Oil (SS75W80)

Nulon Semi-Synthetic 75W-80 Smooth-Shift Manual Gearbox & Transaxle Oil is an extreme pressure API GL-4 premium semi-synthetic gear oil that provides smoother shifting in cold temperatures helps reduce gearbox noise and control idle rattle at higher operating temperatures.

This fluid is recommended for modern vehicles requiring manual transmission fluid or where automatic transmission fluid is recommended in a manual gearbox. Nulon Semi-Synthetic 75W-80 Smooth-Shift Gearbox & Transaxle Oil is also a performance upgrade where a monograde SAE 80 is recommended. Suits Honda, Mazda, Nissan, Suzuki and other manufacturers where GL-4 specification is required.

Recommended for:

Passenger cars: Ferrari, Ford, Holden, Lexus, Lotus, Porsche, Subaru, Toyota and other manufacturers where GL-5 performance is recommended.

Light commercial and 4x4 vehicles: Chrysler, Ford, Holden, Hyundai, Kia, Land Rover, Mazda, Mitsubishi, Nissan, Ssangyong, Suzuki, Toyota and other manufacturers where GL-5 performance is recommended.

Benefits:

- Excellent wear protection
- Superior oil film strength when compared to conventional mineral oil
- Improved protection for synchronisers during heavy load
- Easier low temperature shifting
- Thermal stability to withstand varied operating temperatures



Typical Characteristics

Typical Characteristics	SS75W80 (new)
SAE Viscosity Grade	75W-80
KV @ 100°C, cSt	7.540
KV @ 40°C, cSt	53.23
Viscosity Index	107
Density @ 15°C, g/mL	0.8664
Pour Point, °C	-39
Brookfield Viscosity @-40°C, cP	124000

NOTE: If you are unsure of your vehicles requirements, consult your owners handbook or visit Nulon's extensive product information website www.nulon.com.au or the reference chart where fluids are sold.

Health and Safety

SAFETY DIRECTIONS: Avoid prolonged and repeated skin contact with used oil. During handling, wear suitable gloves and wash hands thoroughly after use. If skin contact occurs wash immediately with soap and water.

FIRST AID: For advice, contact a Poisons Information Centre (Phone: Australia 131 126; New Zealand 0800 764 766) or a doctor (at once).

Use where the following specifications are required	
American Petroleum Institute	API GL-4
Ford	ESW-M2C-83A/B
GM Claims	HN 1046, HN 1070, HN 1820
US Military	MIL-L-2105
ZF Specifications	ZF TE-ML-01, ZF TE-ML-08

Pack Sizes



Part No: SS75W80-1E
1 Litre - 4 per carton
Barcode: 9311090005440



Part No: SS75W80-20
20 litres - Single Unit
Barcode: 9311090004184