

2 in 1 Power Steering Fluid with Stop Leak (PSFSL)

Nulon 2 in 1 Power Steering Fluid with Stop Leak (PSFSL) has been specifically formulated to stop or minimise fluid leaks and maintain optimum performance of power steering systems. This power steering fluid contains seal swell additives that rejuvenate hardened or shrunken seals to prevent further leaks. One treatment stops most leaks.

Power steering systems are generally very reliable and failures are rare, so preventative maintenance is often neglected. Manufacturers rarely mention power steering maintenance in their service schedules. A little preventative maintenance goes a long way to ensuring trouble free operation. Inspections should be carried out at each service. Fluid level should be checked and the fluid should also be checked for cleanliness. If the fluid is dirty it should be changed, as dirt and sludge are major threats to smooth operation. Also, drive belts should be checked for condition and correct tension. Pulleys, mounting brackets and hoses should be checked for condition as well.

Power steering systems typically contain only a small volume of lubricating fluid, and that fluid is subjected to quite harsh conditions, particularly heat, moisture and contamination. Removing old, dirty and degraded power steering fluid and replacing it can extend the life of the entire power steering system. Use Nulon PSFSL for preventative maintenance. Its additional cleaning detergents maintain the durability and integrity of the power steering unit.

Benefits

- Stops leaks fast
- Use as a complete fill or top-up
- Excellent anti-corrosion protection
- Provides additional anti-wear protection
- Suitable for most power steering systems
- Helps eliminate power steering chatter



Directions for use

With engine turned off, fill power steering reservoir to specified level. To stop most leaks keep topping up as necessary with Nulon PSFSL, or for a faster result completely drain existing power steering fluid and replace with this product. Follow directions given in owner's manual for adding fluid.

Do not overfill. If leak persists after a few weeks it indicates a mechanical fault. After using this product, always wash exposed skin thoroughly with soap and water

Note: If your vehicle requires a specialised fluid such as SAAB 4634, MB 236.3, Audi/VW G 002 000, or Honda Type S or V; use Nulon Multi Vehicle Power Steering Fluid (Part No. PSFMV)

Typical Properties

Physical Properties	Typical Values
Kinematic Viscosity @100°C, cst	7.010
Kinematic Viscosity @40°C, cst	31.80
Viscosity Index, ASTM D2270	192
Density @15°C, ASTM D4052, kg/L	0.8555
Pour point, ASTM D97, °C	-40
Flash Point, ASTM D92, °C	200

Pack Sizes



Part No: PSFSL450
500 ml - 6 Per Carton
Barcode: 9311090002296



Part No: PSFSL-1
1 Litre - 6 Per Carton
Barcode: 9311090004849