

## Full Synthetic 0W-20 Fuel Saving Engine Oil (SYNOW20)

Nulon Full Synthetic 0W-20 Fuel Saving Engine Oil is designed to provide the ultimate protection for all new generation passenger cars and light commercial engines that require ultra-low viscosity 0W-20 engine oil. Nulon Full Synthetic 0W-20 Fuel Saving Engine Oil is specifically formulated to provide optimum fuel economy while maintaining the highest level of engine protection over long oil drain intervals and cold start-up conditions.

Nulon Full Synthetic 0W-20 Fuel Saving Engine Oil contains Molybdenum Dithiocarbamate (Moly DTC). Moly DTC is scientifically proven to dramatically reduce friction and provide improved protection against engine wear from cold start to extreme temperatures, ensuring your vehicle is performing how it was designed to.

### Benefits

- Contains Moly DTC for reduced friction and improved protection
- Promotes superior fuel economy
- Ultra-fast flowing formula
- Provides excellent engine cleanliness

NOTE: Refer to your vehicle service manual for correct lubrication requirements and service intervals.



### Typical Characteristics

SAE Viscosity Grade	0W-20
Viscosity @ 100°C (cSt) ASTM D445	8.5
Viscosity @ 40°C (cSt) ASTM D445	43.55
Apparent Viscosity by CCS @ -35°C (cP) ASTM 5293	5100
Apparent Viscosity by MRV @ -40°C (cP) ASTM 4684	22700
Viscosity Index ASTM D2270	176
Density @ 15°C (kg/L) ASTM D4052	0.8503
Sulphated Ash (weight %) ASTM D874	0.947
Total Base Number (mg KOH/g) ASTM D2896	7.4
Flash Point (°C) ASTM D92	>200

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

Meets or exceeds the following oil industry specifications	
American Petroleum Institute	API SN, API SM, API SL, API SJ, API SG
Compatible Fuels	Petrol
Ford	Ford WSS M2C 945A, Ford WSS M2C 947A
ILSAC	ILSAC GF-5
Society of Automotive Engineers	SAE 0W-20

### Pack Sizes



Part No: SYNOW20-5  
5 litres - 3 Per Carton  
Barcode: 9311090004955