

Full Synthetic 10W-60 Extreme Performance Engine Oil

Nulon Full Synthetic 10W-60 Extreme Engine Oil is designed to provide extreme engine protection for high-performance turbocharged, supercharged and large bore naturally aspirated engines during high-stress street and track conditions. Nulon Full Synthetic 10W-60 Extreme Performance Engine Oil ensures maximum protection and performance from cold start to high operating temperatures and high load conditions.

Nulon Full Synthetic 10W-60 Extreme Performance Engine Oil has added Molybdenum Dithiocarbamate (Moly DTC) to give you additional peace of mind performance. Moly DTC is proven to dramatically reduce friction and provide increased engine wear protection from cold start to extreme temperatures, giving you additional benefits over standard engine oil additives alone. For further information go to www.lessfriction.com.au

Benefits

- Extreme engine protection for high performance and race tuned engines
- High Zinc and Moly DTC for increased protection of valve train and turbo bearings
- Increased protection for camshafts, roller rockers and bearings
- Suitable for 4, 6 and 8 cylinder petrol and diesel engines
- Enhanced protection for E85 fuels
- Perfect for high-stress street or track driving
- Full Synthetic Styrene-diene star polymers maintain high shear stability
- Fast flowing formula for superior cold start protection

NOTE: Not recommended for heavy-duty diesel engines. Refer to your vehicle service manual for correct lubrication requirements and service intervals.



Typical Characteristics

SAE Viscosity Grade	10W-60
Viscosity @ 100°C (cSt) ASTM D445	24.02
Viscosity @ 40°C (cSt) ASTM D445	182.1
Apparent Viscosity by CCS @ -25°C (cP) ASTM D5293	6360
Apparent Viscosity by MRV @ -30°C (cP) ASTM D4684	49000
Viscosity Index ASTM D2270	162
Density @ 15°C (kg/L) ASTM D4052	0.8628
Sulphated Ash (mass %) ASTM D874	1.1
Total Base Number (mg KOH/g) ASTM D2896	10.1
Flash Point (°C) ASTM D92	222

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

Caution

CAUTION: Avoid skin contact with used oil. Wear suitable gloves. If skin contact occurs wash immediately with soap and water. Avoid prolonged and repeated contact with used oil. Protect the environment. Do not pollute drains, ground or water with used engine oils. Dispose of container as per EPA guidelines. Do not use this container for fuel or solvents.

Meets or exceeds the following oil industry specifications	
American Petroleum Institute	API SN, API SM, API SL, API SJ, API SG, API CF
Blend Type	Full Synthetic
Compatible Fuels	E85, Light duty diesel, LPG, Petrol
Moly DTC	Contains Moly DTc
Society of Automotive Engineers	SAE 10W-60

Pack Sizes



Part No: SYN10W60-5
5 litres - 3 Per Carton
Barcode: 9311090003378