

## Full Synthetic 15W-50 Street and Track High Performance Engine Oil

Nulon Full Synthetic 15W-50 Street & Track High Performance Engine Oil is recommended for use in high-performance V8 (including large bore), 6 and 4 cylinder engines, where the added protection of a high viscosity oil is required. Enhanced protection for vehicles using E10, E85 and LPG fuels.

Nulon Full Synthetic 15W-50 Street & Track High Performance Engine Oil has added Molybdenum Dithiocarbamate (Moly DTC) to give you additional peace of mind performance. Moly DTC is proven to dramatically reduce friction and provide increased engine wear protection from cold start to extreme temperatures, giving you additional benefits over standard engine oil additives alone. For further information go to [www.lessfriction.com.au](http://www.lessfriction.com.au)

### Benefits

- Ultimate engine protection for high-performance engines during hard street and track driving.
- Higher viscosity shear stable formula for ultimate high-temperature stability.
- For petrol, diesel and LPG engines with 4, 6 and 8 cylinders.
- Enhanced protection for vehicles using E10, E85 and LPG fuels.
- Premium anti-oxidant formula.
- 15W-50 viscosity provides improved oil film strength.
- Added Molybdenum Dithiocarbamate provides more protection and performance over standard engine oil alone.
- Perfect for street or race track use

**NOTE** Not recommended for heavy-duty diesel engines. Refer to your vehicle service manual for correct lubricant requirements and service intervals.



### Typical Characteristics

SAE Viscosity Grade	15W-50
Viscosity @ 100°C (cSt) ASTM D445	18.92
Viscosity @ 40°C (cSt) ASTM D445	132.5
Apparent Viscosity by CCS @ -20°C (cP) ASTM D5293	3180
Apparent Viscosity by MRV @ -25°C (cP) ASTM D4684	16400
Viscosity Index ASTM D2270	162
Density @ 15°C (kg/L) ASTM D4052	0.8613
Sulphated Ash (mass %) ASTM D874	1.0
Total Base Number (mg KOH/g) ASTM D2896	9.5
Flash Point (°C) ASTM D92	230

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

### Caution

**CAUTION** Avoid skin contact with used oil. Wear suitable gloves. If skin contact occurs, wash immediately with soap and water. Avoid prolonged and repeated contact with used oil. Protect the environment. Do not pollute drains, ground or water with used oil. Dispose of container as per EPA guidelines. Do not use this container for fuel or solvents.

### Meets or exceeds the following oil industry specifications

ACEA	ACEA A3/B3-12, ACEA A3/B4-12
American Petroleum Institute	API SN, API SM, API SL, API SJ, API SG, API CF
Blend Type	Full Synthetic
Compatible Fuels	E85, Light duty diesel, LPG, Petrol
Mercedes Benz	MB 229.3, MB 229.5
Moly DTC	Contains Moly DTc
Society of Automotive Engineers	SAE 15W-50
VW	VW 502.00, VW 505.00

### Pack Sizes



**Part No: SYN15W50-5**  
5 litres - 3 Per Carton  
Barcode: 9311090001145



**Part No: SYN15W50-1**  
1 Litre - 6 Per Carton  
Barcode: 9311090000032