

Full Synthetic 5W-30 C4 Performance Diesel Engine Oil

Nulon Full Synthetic 5W-30 C4 Performance Diesel Engine Oil is designed to meet the demanding requirements of the modern high performance diesel engine. Delivering improved fuel efficiency, Nulon 5W-30 C4 Performance Engine Oil is a low SAPS formulation suited to the latest low emission diesel engine vehicles providing the ultimate in engine wear protection over longer drain intervals.

Nulon Full Synthetic 5W-30 C4 Performance Diesel Engine Oil contains Molybdenum Dithiocarbamate (Moly DTc). Moly DTc is scientifically proven to dramatically reduce friction and provide improved protection against engine wear from cold start to extreme temperatures, ensuring your vehicle is performing how it was designed to.

Benefits

- Contains Moly DTc for reduced friction and improved protection
- Energy and fuel conserving formula
- Oil stays cleaner and in-spec for longer
- Low SAPS to maximise Diesel Particulate Filter (DPF) life
- Provides excellent engine cleanliness

NOTE: Not recommended for heavy-duty diesel engines. Refer to your vehicle service manual for correct lubrication requirements and service intervals.



Typical Characteristics

SAE Viscosity Grade	5W-30
Viscosity @ 100°C (cSt) ASTM D445	12.32
Viscosity @ 40°C (cSt) ASTM D445	71.59
Apparent Viscosity by CCS @ -30°C (cP) ASTM D5293	5900
Apparent Viscosity by MRV @ -35°C (cP) ASTM D4684	25500
Viscosity Index ASTM D2270	171
Density @ 15°C (kg/L) ASTM D4052	0.855
Sulphated Ash (weight %) ASTM D874	0.500
Total Base Number (mg KOH/g) ASTM D2896	6.1
Flash Point (°C) ASTM D92	>220



Part No: SYNDC45W30-10
10 litres - Single Unit
Barcode: 9311090004924

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

Cautions

CAUTION: Avoid skin contact with used oil. Wear suitable gloves. If skin contact occurs, wash immediately with soap and water. Avoid prolonged and repeated contact with used oil. Protect the environment. Do not pollute drains, ground or water with used oil.

Dispose of container as per EPA guidelines. Do not use this container for fuel or solvents.

Meets or exceeds the following oil industry specifications	
ACEA	ACEA C4
Compatible Fuels	Light duty DI diesel, Light duty diesel, Petrol
Key Feature	DPF Safe, Low SAPS
Mercedes Benz	MB 226.51
Renault	RN 0720
Society of Automotive Engineers	SAE 5W-30

Suitable for use in the following manufacturers

Jaguar
Land Rover
Mercedes Benz
Nissan
Range Rover
Renault
Suzuki
Volvo

Pack Sizes