

Full Synthetic 5W-30 European Engine Oil (EURO5W30)

Nulon Full Synthetic 5W-30 European Engine Oil is approved under VW Standard 504.00 and VW Standard 507.00 for Volkswagen, Audi, Skoda and Seat petrol and diesel vehicles within manufacturer warranty periods.

PAO base stocks matched with advanced high-performance additives create the ultimate engine oil for these modern European engines during long drain service intervals.

Recommended for use in modern turbocharged, supercharged and normally aspirated diesel and petrol engines that require the highest level of protection and performance. This oil is also suitable for vehicles fitted with Diesel Particulate Filters (DPF's).

Benefits

- Designed for modern European petrol and diesel engines
- [Approved for VW 504.00 petrol and 507.00 diesel specifications](#)
- Suitable for modern-diesels fitted with Diesel Particulate Filters (DPF) and petrol engines fitted with Catalytic Converters (CATS)
- Enhanced engine protection during recommended long oil drain intervals
- Maintains viscosity under high-load and temperature conditions
- Provides superior cold start-up protection
- Energy/fuel conserving formula
- Provides excellent engine cleanliness
- Superior oxidation control and thermal stability

NOTE Not recommended for heavy-duty diesel engines. Refer to your vehicle service manual for correct lubrication requirements and service intervals.



Typical Characteristics

SAE Viscosity Grade	5W-30
Viscosity @ 100°C (cSt) ASTM D445	12.04
Viscosity @ 40°C (cSt) ASTM D445	76.39
Apparent Viscosity by CCS @ -30°C (cP) ASTM 5293	6220
Apparent Viscosity by MRV @ -35°C (cP) ASTM 4684	16600
Viscosity Index ASTM D2270	154
Density @ 15°C (kg/L) ASTM D4052	0.8537
Sulphated Ash (mass %) ASTM D874	0.5
Total Base Number (mg KOH/g) ASTM D2896	5.4
Flash Point (°C) ASTM D92	227

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

Caution

Avoid skin contact with used engine oils. Wear suitable gloves. If skin contact occurs wash immediately with soap and water. Avoid prolonged and repeated contact with used oil. Protect the environment. Do not pollute drains, ground or water with used engine oils. Dispose of container as per EPA guidelines. Do not use this container for fuel or solvents.

Meets or exceeds the following oil industry specifications

ACEA	ACEA C3
American Petroleum Institute	API SN, API SM, API SL
Blend Type	Full Synthetic
BMW	BMW LL-04
Compatible Fuels	Light duty diesel, Petrol
Key Feature	Low SAPS
Mercedes Benz	MB 229.51
Society of Automotive Engineers	SAE 5W-30
VW	VW 504.00, VW 507.00

Suitable for use in the following manufacturers Models or exceeds the following industry specifications

Audi
BMW
Mercedes Benz
Skoda
Volkswagen

Pack Sizes



Part No: EURO5W30-1
1 Litre - 6 Per Carton
Barcode: 9311090002753



Part No: EURO5W30-5
5 litres - 3 Per Carton
Barcode: 9311090002760



Part No: EURO5W30-20
20 litres - Single Unit
Barcode: 9311090003026