

## Full Synthetic 5W-30 Long Life Formula Diesel Engine Oil (SYND5W30)

Nulon Full Synthetic 5W-30 Formula Long Life Diesel Engine Oil is a dexos2® approved formula designed to provide the ultimate protection for all technically-advanced passenger car and light commercial petrol and diesel engines.

Specifically formulated for vehicles that require a fuel conserving 5W-30 low viscosity engine oil while at the same time needing enhanced protection during long oil drain intervals. Safe to use in modern diesel engines fitted with catalysts and Diesel Particulate Filters (DPF). These engines require an engine oil with a low Sulphated-Ash, Phosphorus and Sulphur content (Mid SAPS).

Recommended for use in both turbocharged and non-turbocharged diesel and petrol engines.

### Benefits

- Ultimate protection for modern car and light commercial diesel engines
- Low viscosity ensures maximum fuel efficiency
- [dexos2® approved License RB2C1214095](#)
- Recommended for modern diesels fitted with Diesel Particulate Filters (DPF)
- Provides excellent cold start-up protection
- Fast flowing low viscosity formula
- Energy conserving
- Provides excellent engine cleanliness
- Provides excellent oxidation control and thermal stability
- Oil stays in-spec during long oil drain intervals



### Typical Characteristics

SAE Viscosity Grade	5W-30
Viscosity @ 100°C (cSt) ASTM D445	11.57
Viscosity @ 40°C (cSt) ASTM D445	69.56
Apparent Viscosity by CCS @ -30°C (cP) ASTM D5293	6160
Apparent Viscosity by MRV @ -35°C (cP) ASTM D4684	36600
Viscosity Index ASTM D2270	161
Density @ 15°C (kg/L) ASTM D4052	0.8509
Sulphated Ash (mass %) ASTM D874	0.8
Total Base Number (mg KOH/g) ASTM D2896	7.8
Flash Point (°C) ASTM D92	246

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

### Warnings

NOTE: Not recommended for heavy-duty diesel engines. Refer to your vehicle service manual for correct lubrication requirements and service intervals.

CAUTION: Avoid skin contact with used engine oils. Wear suitable gloves. If skin contact occurs wash immediately with soap and water. Avoid prolonged and repeated contact with used oil. Protect the environment. Do not pollute drains, ground or water with used engine oils. Dispose of container as per EPA guidelines. Do not use this container for fuel or solvents.

Meets or exceeds the following oil industry specifications	
ACEA	ACEA C3
American Petroleum Institute	API SN, API SM, API SH, API SL, API SJ, API SG, API CF
Blend Type	Full Synthetic
BMW	BMW LL-04
Compatible Fuels	Light duty DI diesel, Light duty diesel, Petrol
GM	dexos2® approved. License RB2C1214095
Key Feature	DPF Safe, Mid SAPS

### Meets or exceeds the following oil industry specifications

Mercedes Benz	MB 226.5, MB 229.31, MB 229.51
Society of Automotive Engineers	SAE 5W-30
VW	VW 502.00, VW 505.01

### Suitable for use in the following manufacturers

Ford  
Holden  
Hyundai  
Land Rover  
Mitsubishi  
Nissan  
Range Rover  
Ssangyong  
Subaru  
Toyota

### Pack Sizes



Part No: SYND5W30-1  
1 Litre - 6 Per Carton  
Barcode: 9311090002661



Part No: SYND5W30-5  
5 litres - 3 Per Carton  
Barcode: 9311090000001



Part No: SYND5W30-7  
7 Litres - 2 per carton  
Barcode: 9311090006263



Part No: SYND5W30-10  
10 litres - Single Unit  
Barcode: 9311090000070



Part No: SYND5W30-20  
20 litres - Single Unit  
Barcode: 9311090000087