

## Full Synthetic 5W-30 Long Life Performance Engine Oil (SYN5W30)

Nulon Full Synthetic 5W-30 Long Life Performance Engine Oil provides the maximum protection and performance from cold start-up to high operating temperatures. The energy conserving, low viscosity formula ensures optimum engine performance for all technically advanced and performance passenger car petrol engines.

The ILSAC GF-5 energy conserving formulation delivers improved fuel economy and engine protection. Additional anti-wear additives provide maximum performance and protection to engine and turbocharger components, while enhanced corrosion protection provides bio-fuel compatibility for vehicles using E10 and E85 fuels.

### Benefits

- Meets Holden and HSV warranty requirements where dexos1® 5W-30 is specified
- Oil stays cleaner and in-spec for longer
- Energy and fuel conserving formula
- Provides excellent engine cleanliness
- Reduces turbocharger deposit build-up
- Compatible with biofuels (Ethanol E10 and E85)



NOTE: Not recommended for diesel engines or vehicles fitted with [DPF](#). Refer to your vehicle service manual or Nulon lube guide for correct lubrication requirements and service intervals.

### Typical Characteristics

SAE Viscosity Grade	5W-30
Viscosity @ 100°C (cSt) ASTM D445	10.66
Viscosity @ 40°C (cSt) ASTM D445	63.92
Apparent Viscosity by CCS @ -30°C (cP) ASTM 5293	6020
Apparent Viscosity by MRV @ -35°C (cP) ASTM 4684	16800
Viscosity Index ASTM D2270	157
Density @ 15°C (kg/L) ASTM D4052	0.8525
Sulphated Ash (mass %) ASTM D874	0.9
Total Base Number (mg KOH/g) ASTM D2896	8.5
Flash Point (°C) ASTM D92	236

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

### Caution

CAUTION: Avoid skin contact with used oil. Wear suitable gloves. If skin contact occurs, wash immediately with soap and water. Avoid prolonged and repeated contact with used oil. Protect the environment. Do not pollute drains, ground or water with used oil.

Dispose of container as per EPA guidelines. Do not use this container for fuel or solvents.

### Meets or exceeds the following oil industry specifications

American Petroleum Institute	API SN, API SM, API SL, API SJ, API SG
Blend Type	Full Synthetic
Chrysler	Chrysler MS 6395
Compatible Fuels	E85, LPG, Petrol
Ford	Ford WSS M2C 946A
GM	6094M, dexos1® approved. License D10446HH095, GM 4718M, GM-LL-A-025
ILSAC	ILSAC GF-5
Society of Automotive Engineers	SAE 5W-30

### Suitable for use in the following manufacturers

Chrysler  
Ford

Holden  
Honda  
Kia  
Lexus  
Mazda  
Mitsubishi  
Nissan  
Subaru  
Suzuki  
Toyota

### Pack Sizes



Part No: SYN5W30-1  
1 Litre - 6 Per Carton  
Barcode: 9311090002708



Part No: SYN5W30-5  
5 litres - 3 Per Carton  
Barcode: 9311090002715



Part No: SYN5W30-SIX  
6 litres - 3 Per Carton  
Barcode: 9311090003651



Part No: SYN5W30-10  
10 litres - Single Unit  
Barcode: 9311090002722



Part No: SYN5W30-20  
20 litres - Single Unit  
Barcode: 9311090003019