

Full Synthetic 5W-30 Low Emission Diesel Engine Oil (SYNDLE5W30)

Nulon Full Synthetic 5W-30 Low Emission Diesel Engine Oil offers the ultimate protection for the modern diesel vehicle fitted with a Diesel Particulate Filter (DPF). Nulon Full Synthetic 5W-30 Low Emission Diesel Engine Oil combines optimal fuel efficiency with an ultra-low SAPS formulation for modern low emission diesel engine vehicles.

Nulon Full Synthetic 5W-30 Low Emission Diesel Engine Oil contains Molybdenum Dithiocarbamate (Moly DTc). Moly DTc is scientifically proven to dramatically reduce friction and provide improved protection against engine wear from cold start to extreme temperatures, ensuring your vehicle is performing how it was designed to.

Benefits

- Contains Moly DTc for reduced friction and improved protection
- Energy and fuel conserving formula
- Ultra-low SAPS formula for longer Diesel Particulate Filter (DPF) life
- Oil stays cleaner and in-spec for longer
- Provides excellent engine cleanliness

NOTE: Not recommended for heavy-duty diesel engines. Refer to your vehicle service manual for correct lubrication requirements and service intervals.



Typical Characteristics

SAE Viscosity Grade	5W-30
Viscosity @ 100°C (cSt) ASTM D445	10.84
Viscosity @ 40°C (cSt) ASTM D445	63.26
Apparent Viscosity by CCS @ -30°C (cP) ASTM D5293	5510
Apparent Viscosity by MRV @ -35°C (cP) ASTM D4684	31900
Viscosity Index ASTM D2270	164
Density @ 15°C (kg/L) ASTM D4052	0.8551
Sulphated Ash (weight %) ASTM D874	0.500
Total Base Number (mg KOH/g) ASTM D2896	6.23
Flash Point (°C) ASTM D92	>220

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

Caution

Avoid skin contact with used oil. Wear suitable gloves. If skin contact occurs, wash immediately with soap and water. Avoid prolonged and repeated contact with used oil. Protect the environment. Do not pollute drains, ground or water with used oil. Dispose of container as per EPA guidelines. Do not use this container for fuel or solvents.

Meets or exceeds the following oil industry specifications	
ACEA	ACEA C1
Compatible Fuels	Light duty DI diesel, Light duty diesel, Petrol
JASO	DL-1
Key Feature	DPF Safe, Low SAPS, Ultra-low SAPS
Society of Automotive Engineers	SAE 5W-30

Suitable for use in the following manufacturers

Citroen
Mazda
Mitsubishi
Peugeot
Renault

Pack Sizes



Part No: SYNDLE5W30-1
1 Litre - 6 Per Carton
Barcode: 9311090004948



Part No: SYNDLE5W30-5
5 litres - 3 Per Carton
Barcode: 9311090004931