

Full Synthetic 75W-85 Differential Transfer Case & Transaxle Oil (LSD75W85)

NULON Full Synthetic SAE 75W-85 Differential, Transfer Case & Transaxle Oil is an extreme pressure API GL-5 full synthetic hypoid gear oil that provides superior wear protection and high temperature stability.

Ideal for use in transaxles, transfer cases and hypoid differentials. It is suitable for both conventional and limited slip differentials.

Passenger cars, 4x4, SUV and Light Commercial Vehicles: Chrysler/Jeep, Honda, Lexus, Mercedes, Mitsubishi, Toyota and other Manufacturers where GL-5 performance is recommended.

Meets or exceeds the following specifications:

- API GL-5
- API MT-1
- Mack GO-J
- MIL-L-2105B/C/D, MIL-PRF-2105E
- SAE J2360

NOTE: If you are unsure of your vehicle requirements, consult your owner's handbook or visit Nulon's extensive product information website www.nulon.com.au.



Safety

SAFETY DIRECTIONS: Avoid prolonged and repeated skin contact with used oil. During handling, wear suitable gloves and wash hands thoroughly after use. If skin contact occurs wash immediately with soap and water.

FIRST AID: For advice, contact a Poisons Information Centre (Phone: Australia 131 126; New Zealand 0800 764 766) or a doctor (at once).

Meets or exceeds the following oil industry specifications	
American Petroleum Institute	API GL-5, API MT-1
Mack	Mack GO-J
Society of Automotive Engineers	SAE J2360
US Military	MIL-L-2105 B, MIL-L-2105 C, MIL-L-2105 D, MIL-PRF-2105E

Pack Sizes



Part No: LSD75W85-1E
1 Litre - 4 per carton
Barcode: 9311090005655



Part No: LSD75W85-20
20 litres - Single Unit
Barcode: 9311090005686