

Green Radiator Corrosion Protector

Nulon Radiator Corrosion Protector - protects your cooling system from rust and corrosion for 3 years or 100,000km no matter the age or metal type. NOTE: For vehicles that require a Type A OEM replacement coolant use Nulon Long Life Coolants, available in both Concentrate and Pre-Mixed variants.

Benefits

- Contains advanced long life inhibitor technology for maximum corrosion protection of all cooling system metals for 3 years or 100,000km
- Built in Water Wetter promotes quicker heat reduction over conventional coolant
- Protects aluminium, steel, cast iron, solder, copper and brass
- Safe for all hoses, gaskets and seals
- Exceeds Australian AS 2108-2004 Type B standard



Directions for use

DIRECTIONS FOR SERVICE REFILL: Refer to the owner's manual for cooling system capacity. If the cooling system is dirty we recommended using Nulon Radiator Flush before using this product.

1. If the system is clean, ensure the engine is switched off, turn the heater on and drain the old coolant (when cool) by removing the drain plug or bottom radiator hose.
2. Replace drain plug or bottom radiator hose.
3. Add NULON RADIATOR CORROSION PROTECTOR to the radiator first then top-up with clean, soft or demineralised water. (Makes up to 15 Litres)
4. Check the coolant level is correct when system is cool.

Safety Direction

SAFETY DIRECTION: Harmful if swallowed. DO NOT SWALLOW. Keep out of reach of children. Not to be used as a food container. If spilt on paintwork, wash off immediately with water. To protect the environment, dispose of used coolant in a safe manner or as advised by the Environmental Protection Agency.

FIRST AID: If poisoning occurs contact a doctor or the Poisons Information Centre in Australia 131 126 or New Zealand 0800 764 766. If swallowed, do NOT induce vomiting. If in eyes, hold eyelids apart and flush the eye continuously with running water. If skin contact occurs, flush with running water.

Meets or exceeds the following oil industry specifications

AS Claims	AS 2108-2004 Type B
ASTM	ASTM D3306, ASTM D4985
Society of Automotive Engineers	SAE J1034, SAE J1941

Pack Sizes



Part No: RCPG-1
1 Litre - 6 Per Carton
Barcode: 9311090 004696



Part No: RCPG-500
500 ml - 6 Per Carton
Barcode: 9311090 004825