

Mineral 15W-40 Everyday Diesel Engine Oil

Nulon Mineral 15W-40 Everyday Diesel Engine Oil is blended to meet API CH-4/SJ specifications. Premium base oils combined with detergents prevent oil thickening and soot build-up which keeps the engine cleaner and cooler for longer. Nulon Mineral 15W-40 Everyday Diesel Engine Oil also protects critical engine components from other harmful substances created during combustion. Formulated to provide an excellent level of protection for diesel engines, large or small, non-turbocharged and turbocharged.

For superior protection and performance use [Nulon Semi Synthetic 15W-40 High Torque Protection Diesel Engine Oil \(Part No. SSD15W40\)](#).

Benefits

- Designed to protect critical engine components from wear and tear
- Keep internals cool while reducing soot and deposits during continuous heavy torque loads
- For light diesel and heavy-duty diesel vehicles, both direct and indirect injection engines
- Suits both turbocharged and non-turbocharged diesel engines
- Suitable for LPG and dual fuel systems
- Ideal for fleet use



Typical Characteristics

SAE Viscosity Grade	15W-40
Viscosity @ 100°C (cSt) ASTM D445	14.98
Viscosity @ 40°C (cSt) ASTM D445	123
Apparent Viscosity by CCS @ -20°C (cP) ASTM D5293	6420
Apparent Viscosity by MRV @ -25°C (cP) ASTM D4684	23780
Viscosity Index ASTM D2270	125
Density @ 15°C (kg/L) ASTM D4052	0.8747
Sulphated Ash (mass %) ASTM D874	1.5
Total Base Number (mg KOH/g) ASTM D2896	8.6
Flash Point (°C) ASTM D92	232

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

Warnings

NOTE: Not suitable for vehicles fitted with Diesel Particulate Filters (DPF). Refer to your vehicle service manual for correct lubricant requirements and service intervals.

CAUTION: Avoid skin contact with used oil. Wear suitable gloves. If skin contact occurs, wash immediately with soap and water. Avoid prolonged and repeated contact with used oil. Protect the environment. Do not pollute drains, ground or water with used oil. Dispose of container as per EPA guidelines. Do not use this container for fuel or solvents.

Meets or exceeds the following oil industry specifications

American Petroleum Institute	API CH-4, API CG-4, API SH, API SJ, API SG
Blend Type	Mineral
Compatible Fuels	CNG, Dual-Fuel, Heavy Duty Diesel, LPG, Petrol
Cummins	Cummins 20076
MAN Claims	MAN 270
Mercedes Benz	MB 228.1, MB 228.3
Other Claims	MAN 271, MAN M3275, MTU Type 1, MTU Type 2
Society of Automotive Engineers	SAE 15W-40

Pack Sizes



Part No: ED15W40-10
10 litres - Single Unit
Barcode: 9311090003897



Part No: ED15W40-20
20 litres - Single Unit
Barcode: 9311090003903