

Mineral 20W-50 Super Diesel Engine Oil (OD20W50)

Nulon Mineral 20W-50 Super Diesel Engine Oil is formulated to provide the highest level of protection for old or worn diesel engines, large or small, non-turbocharged and turbocharged. It is ideally suited to vehicles that have travelled higher kilometres and require the added wear protection or oil loss prevention of a higher viscosity engine oil. Nulon Mineral 20W-50 Super Diesel Engine Oil can also be used in higher ambient temperatures or prolonged hot running conditions.

Meets the requirements of API CH-4/SJ

Nulon Mineral 20W-50 Super Diesel Engine Oil is ideal for older mixed fleet use for vehicles not requiring a Low SAPS oil.

Benefits

- Formulated for older high kilometre diesel engines requiring extra protection
- Thicker viscosity slows oil loss and burning in worn diesel engines
- Greater engine protection for older diesel engines and high temperature conditions
- Suitable for all, turbocharged and non-turbocharged diesel engines
- Provides superior protection for LPG, CNG and dual-fuel system vehicles
- Minimises sludge deposits to keep your engine cleaner
- Superior deposit control reduces soot and prolongs engine life
- Reduces oil consumption and the need for regular top-up
- Ideal for older fleet use



Typical Characteristics

SAE Viscosity Grade	20W-50
Viscosity @ 100°C (cSt) ASTM D445	18.92
Viscosity @ 40°C (cSt) ASTM D445	180.1
Apparent Viscosity by CCS @ -15°C (cP) ASTM D5293	8740
Apparent Viscosity by MRV @ -20°C (cP) ASTM D4684	26500
Viscosity Index ASTM D2270	119
Density @ 15°C (kg/L) ASTM D4052	0.8832
Sulphated Ash (mass %) ASTM D874	1.0
Total Base Number (mg KOH/g) ASTM D2896	9.5
Flash Point (°C) ASTM D92	226

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

Warnings

NOTE: Not suitable for vehicles fitted with Diesel Particulate Filters (DPF). Refer to your vehicle service manual for correct lubricant requirements and service intervals.

CAUTION: Avoid skin contact with used oil. Wear suitable gloves. If skin contact occurs, wash immediately with soap and water. Avoid prolonged and repeated contact with used oil. Protect the environment. Do not pollute drains, ground or water with used oil.

Dispose of container as per EPA guidelines. Do not use this container for fuel or solvents.

Meets or exceeds the following oil industry specifications	
American Petroleum Institute	API CH-4, API CG-4, API CF-4, API SH, API SJ, API SG
Blend Type	Mineral
Compatible Fuels	CNG, Dual-Fuel, Heavy Duty Diesel, LPG, Petrol
Society of Automotive Engineers	SAE 20W-50



Part No: OD20W50-10
10 litres - Single Unit
Barcode: 9311090003927

Pack Sizes