

Nulon Multi-Vehicle Coolant Pre-Mix (GPM)

Benefits

- Formulated and made in Australia for Australian conditions
- Contains advanced inhibitor technology for maximum corrosion protection
- Protection of all cooling systems metals for up to 350,000km
- Protects aluminium steel, cast iron, solder, copper and brass
- Provides maximum protection against cavitation damage and cylinder liner pitting
- Safe for all hoses, gaskets and seals
- Exceeds Australian AS 2108-2004 Type A Standard



Directions for use

DIRECTIONS FOR SERVICE REFILL: Refer to the owner's manual for cooling system capacity, we recommend using Nulon Radiator Flush and Clean before using this product. If the system is clean, ensure the engine is switched off, turn the heater on and drain the old coolant (when cool) by removing the drain plug or bottom radiator hose. To completely flush the system, continue to add clean water until all remnants of the old coolant have been flushed from the system. Replace the drain plug or bottom radiator hose. Add Nulon Multi-Vehicle Coolant Pre-Mix to the radiator first (see table below) then top-up with clean, soft or demineralised water. Check the coolant level is correct when system is cool.

WARNING: Never mix coolants from different manufacturers. Never mix green coolant with red or blue. If in doubt, flush the system and do a complete coolant change.

AS TOP-UP TO EXISTING COOLANT: Add as a top-up to existing, then start the engine and turn the heater on. When the engine is warm, turn it off and allow it to cool. Check the coolant level and top-up if necessary. For OEM replacement coolant, please use Nulon Long Life Coolant Pre-Mix (LLTU).

Protection Level	Boils at	Freezes at
350,000km	123°C*	-12.5°C

* using 105kPa radiator cap.

Safety Direction

SAFETY DIRECTION: Harmful if swallowed. DO NOT SWALLOW. Keep out of reach of children. Not to be used as a food container. If spilt on paintwork, wash off immediately with water. To protect the environment, dispose of used coolant in a safe manner or as advised by the Environmental Protection Authority.

FIRST AID: If poisoning occurs contact a doctor or the Poisons Information Centre in Australia 131 126 or New Zealand 0800 764 766. If swallowed, do NOT induce vomiting. If in eyes, hold eyelids apart and flush the eye continuously with running water. If skin contact occurs, flush with running water.

Meets or exceeds the following oil industry specifications	
AS Claims	AS 2108-2004 Type A
ASTM	ASTM D1384, ASTM D2570, ASTM D2809, ASTM D4340

Pack Sizes



Part No: GPM-5
5 litres - 3 Per Carton
Barcode: 9311090006010