

## Green Coolant Premix (GPM)

Nulon Green Coolant Premix provides anti-boil, anti-freeze and corrosion protection for a wide range of vehicle cooling systems requiring a Green Type A Coolant. Designed to suit Australian conditions, the high boil point will provide maximum protection for cooling systems for up to 350,000 km when used as a complete service fill.

### Benefits

- Contains advanced inhibitor technology for maximum corrosion protection of all cooling system metals for up to 350,000 km
- Protects aluminium, steel, cast iron, solder, copper and brass
- Safe for all hoses, gaskets and seals
- Safe for all vehicles requiring a green TYPE A coolant
- Exceeds Australian AS 2108-2004 TYPE A standard



### Directions for use

**DIRECTIONS FOR SERVICE REFILL:** Refer to the owner's manual for cooling system capacity, we recommend using Nulon Radiator Flush and Clean before using this product. If the system is clean, ensure the engine is switched off, turn the heater on and drain the old coolant (when cool) by removing the drain plug or bottom radiator hose. To completely flush the system, continue to add clean water until all remnants of the old coolant have been flushed from the system. Replace the drain plug or bottom radiator hose. Add Nulon Multi-Vehicle Coolant Pre-Mix to the radiator first (see table below) then top-up with clean, soft or demineralised water. Check the coolant level is correct when system is cool.

**WARNING:** Never mix coolants from different manufacturers. Never mix green coolant with red or blue. If in doubt, flush the system and do a complete coolant change.

**AS TOP-UP TO EXISTING COOLANT:** Add as a top-up to existing, then start the engine and turn the heater on. When the engine is warm, turn it off and allow it to cool. Check the coolant level and top-up if necessary. For OEM replacement coolant, please use Nulon Long Life Coolant Pre-Mix (LLTU).

Protection Level	Boils at	Freezes at
350,000km	123°C*	-12.5°C

\* using 105kPa radiator cap.

### Safety Directions

**SAFETY:** Harmful if swallowed. May cause respiratory irritation. Use only outdoors or in a well-ventilated area. Store locked up.

**FIRST AID: IF SWALLOWED:** Immediately call a POISON CENTRE or doctor/physician.

Rinse mouth. **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor (at once).

**ENVIRONMENT:** Avoid release to the environment. Dispose of contents/container in accordance with local council regulations.

Meets or exceeds the following oil industry specifications	
AS Claims	AS 2108-2004 Type A
ASTM	ASTM D1384, ASTM D2570, ASTM D2809, ASTM D4340

### Pack Sizes



Part No: GPM-5  
5 litres - 3 Per Carton  
Barcode: 9311090006010