

ONE 100% Concentrate Coolant

FIRST CHOICE, RIGHT CHOICE, EVERYTIME.

Nulon ONE 100% Concentrate Coolant is the pinnacle of modern coolant technology pioneered by Australia's most trusted and established coolant brand. This **OEM replacement coolant** is suitable for **every make** and **every model** found on Australian and New Zealand roads making this coolant the right choice every time while providing your vehicle a guaranteed **10 years** or **1 million kilometres** of superior anti-freeze/anti-boil and total anti-corrosion protection.

Benefits

- Guaranteed to protect for **10 years** or **1 million kilometres**
- Suitable for **every make** and **every model** of vehicle on Australian and New Zealand roads
- **OEM replacement coolant**
- Provides **Maximum anti-freeze/anti-boil protection**
- Ensures **total anti-corrosion protection** for the entire cooling system
- Exceeds Australian AS 2108-2004 Type A standard, plus international and national vehicle industry standards



Directions for use

DIRECTIONS AS COMPLETE FILL: Refer to the owner's manual for cooling system capacity. We recommend using a NULON Radiator/Cooling System Flush before using this product. This will remove any harmful oil and scale residue.

1. Ensure the engine is switched off, turn the heater on and drain the old coolant (when cool) by removing the drain plug or bottom radiator hose.
2. To completely flush the system, continue to add demineralised water until all remnants of the old coolant have been flushed from the system. Replace drain plug or bottom radiator hose.
3. Add NULON ONE 100% CONCENTRATE COOLANT to the radiator first (see table) then top-up with demineralised water.
4. Check the coolant level is correct when system is cool.
5. Replace NULON ONE 100% CONCENTRATED COOLANT in 10 YEARS or 1,000,000 KMS, whichever comes first.

WARNING: Never mix coolants from different manufacturers. DO not mix Nulon ONE with green, red or blue coolant.

Mix ratio	Makes	Boils at	Freezes at
50%	1 litre makes 2 litres	128°C*	-37°C

* using 105kPa radiator cap.

Typical Properties

Typical Properties:	Values
Density (g/ml @ 15.6oC)	1.122 - 1.128
Freezing point (oC @ 50% v/v solution)	-37
Boiling point * (oC @ 50% v/v solution)	128
pH	8.0 - 9.0
Reserve alkalinity (ml)	5.0 min
Colour	Yellow
Glycol content (g/L)	1090

* using 105kPa radiator cap

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

Safety Direction

SAFETY DIRECTION: Harmful if swallowed. DO NOT SWALLOW. Keep out of reach of children. Not to be used as a food container. If spilt on paintwork, wash off immediately with water. To protect the environment, dispose of used coolant in a safe manner or as advised by the Environmental Protection Agency.

FIRST AID: If poisoning occurs contact a doctor or the Poisons Information Centre in Australia 131 126 or New Zealand 0800 764 766. If swallowed, do NOT induce vomiting. If in eyes, hold eyelids apart and flush the eye continuously with running water. If skin contact occurs, flush with running water.

Meets or exceeds the following oil industry specifications

AS Claims	AS 2108-2004 Type A
ASTM	ASTM D1384, ASTM D2570, ASTM D2809, ASTM D3306, ASTM D4340, ASTM D4656, ASTM D4985, ASTM D5345, ASTM D6210
Audi	Audi G12+, Audi G12, Audi G11
BMW	BMW (UK), N 600 69.0
Caterpillar	Caterpillar 1 EO 535
Chrysler	Daimler Chrysler MS-7170, Daimler Chrysler MS-976
Cummins	Cummins 92 T8-9
Detroit	Detroit Diesel Allison 7SE298
Ford	ESE M97-B18C, ESE M97-B44A, ESE M97-B44D, WSS-M97B44-D
GM	GM 1825M, GM 1889M, GM 1899M, GM 6277M
Holden	HN 2043, HN 2217
Honda	Honda All Season Type 2, Honda Longlife Coolant Type 2, Honda Radiator Coolant Type 2 (Blue)
Madza	Mazda MES MN 1210, Mazda MES MN 121D
Mercedes Benz	MB 325.0, Mercedes Benz DBL 7700
Mitsubishi	Mitsubishi ES-X64217, Mitsubishi Super Long Life Premium Coolant (Blue) part MZ313950
Nissan	Nissan Blue Long Life Antifreeze/Coolant, Nissan NES 5059 LLC, Nissan NES M 5509
Opel	Opel B 040 0240
Other Claims	BS 6580:1992, ETHYLENE-GLYCOL COOLANT 850, FL22, GME L 1301, JIS K2234 (Japan), Mopar Formula HOAT (MS-9769), MWN Diesel D234 2/15
Parafly	Parafly 11, Parafly UP
Saab	SAAB FSD 8704
Society of Automotive Engineers	SAE J1034, SAE J1941
Subaru	Subaru Super Long Life coolant (Blue)
Suzuki	Suzuki Super Long Life coolant (Blue)
Toyota	Toyota K2601G, Toyota K2601G-1G, TOYOTA SUPER LONG LIFE COOLANT
Volvo	Volvo (UK)
VW	VW G12+, VW G12, VW G11, TL-774-C

Meets or exceeds the following oil industry specifications

Pack Sizes



Part No: ONE-5
5 litres - 3 Per Carton
Barcode: 9311090004603



Part No: ONE-2.5
2.5 Litres - 6 Per Carton
Barcode: 9311090004597