

Power Steering Fluid

Nulon Power Steering Fluid (PSF) is a mineral based fluid that has been formulated to suit all power steering systems that require a Dexron® fluid. Nulon PSF contains enhanced anti-corrosion and anti wear additives to ensure optimum protection. It is an excellent everyday choice for Australian conditions.

Power steering systems are generally very reliable and failures are rare, so preventative maintenance is often neglected. Manufacturers rarely mention power steering maintenance in their service schedules. A little preventative maintenance goes a long way to ensuring trouble free operation and long service life. Inspections should be carried out at each service. Fluid level should be checked and the fluid should also be checked for cleanliness. If the fluid is dirty it should be changed, as dirt and sludge are major threats to smooth operation. Also, drive belts should be checked for condition and correct tension. Pulleys, mounting brackets and hoses should be checked for condition as well.

Power steering systems typically contain only a small volume of lubricating fluid, and that fluid is subjected to quite harsh conditions, particularly heat, moisture and contamination. Periodically removing old, dirty and degraded power steering fluid and replenishing it with Nulon Power Steering Fluid will significantly extend the life of the entire power steering system.

Benefits

- Compatible with most power steering systems
- Helps eliminate power steering chatter/shudder
- Contains anti-corrosion & anti-wear protection
- Use as a complete fill or top-up



Directions for Use

Simply add to the power steering system reservoir. Fill the reservoir to the level specified by the max level and do not overfill. Repeat application when necessary, or when the system is serviced.

Typical Properties

Tests	ASTM	PSF
Color	Visual	Red
Flash point, COC, °C	D92	208
Foam characteristics	D892	Nil Foam
Viscosity @ 100°C, cSt	D445	7.020
Viscosity @ 40°C, cSt	D445	32.00
Viscosity index	D2270	191
Density Kg/l	D4052	0.8578
Pour point °C	D97	-40

Specifications

Use Nulon Power Steering Fluid where the following specifications are called for:

- Dexron® II/III
- Ford Mercon
- ZF TE-ML 05L
- ZF TE-ML 09
- ZF TE-ML 14A
- Volvo 97335
- Denison
- Caterpillar TO-2
- Type A Suffix A (TASA)
- Ford M2C 138CJ

Note: If your vehicle requires a specialised fluid such as SAAB 4634, MB 236.3, Audi/VW G 002 000 or Honda Type S or V, use Nulon 100% Synthetic Multi-Vehicle Power Steering Fluid (Part No. PSFMV).

Pack Sizes



Part No: PSF500
500 ml - 6 Per Carton
Barcode: 9311090002401



Part No: PSF-1
1 Litre - 6 Per Carton
Barcode: 9311090002418