

## Premium Mineral 10W-30 Fast Flowing Engine Oil (PM10W30)

Nulon Premium Mineral 10W-30 Fast Flowing Engine Oil provides excellent anti-wear protection for everyday driving. Formulated for multi-valve and turbocharged 4, 6 and 8 cylinder modern petrol and LPG engines, this oil will keep your engine cool, clean and protected.

For additional protection and performance use Nulon Semi Synthetic 10W-30 Hi-Tech Fast Flowing Engine Oil (Part No. HT10W30).

### Benefits

- Blended for modern Australian, Japanese, US and European vehicles
- Provides excellent engine protection for daily driving
- Popular viscosity that provides excellent fuel economy
- Premium virgin mineral base oils provide superior performance and protection for everyday driving
- Excellent thermal stability provides protection from start-up to high operating temperatures and conditions
- Premium detergent and dispersant technology to keep engines clean and protected from sludge
- High shear stable polymers provide optimum control of viscosity until the next oil change
- Suitable as a running-in oil



### Typical Characteristics

SAE Viscosity Grade	10W-30
Viscosity @ 100°C (cSt) ASTM D445	11.53
Viscosity @ 40°C (cSt) ASTM D445	79.05
Apparent Viscosity by CCS @ -25°C (cP) ASTM D5293	6180
Apparent Viscosity by MRV @ -30°C (cP) ASTM D4684	33700
Viscosity Index ASTM D2270	138
Density @ 15°C (kg/L) ASTM D4052	0.8684
Sulphated Ash (mass %) ASTM D874	0.7
Total Base Number (mg KOH/g) ASTM D2896	6.6
Flash Point (°C) ASTM D92	228

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

### Warnings

**NOTE:** Not recommended for heavy-duty diesel engines. Refer to your vehicle service manual for correct lubricant requirements and service intervals.

**CAUTION:** Avoid skin contact with used oil. Wear suitable gloves. If skin contact occurs, wash immediately with soap and water. Avoid prolonged and repeated contact with used oil. Protect the environment. Do not pollute drains, ground or water with used oil. Dispose of container as per EPA guidelines. Do not use this container for fuel or solvents.

### Meets or exceeds the following oil industry specifications

American Petroleum Institute	API SN, API SM, API SH, API SL, API SJ, API SG, API CF
Blend Type	Mineral
Compatible Fuels	E85, Light duty diesel, LPG, Petrol
ILSAC	ILSAC GF-5
Society of Automotive Engineers	SAE 10W-30

### Pack Sizes



Part No: PM10W30-1  
1 Litre - 6 Per Carton  
Barcode: 9311090003682



Part No: PM10W30-5  
5 litres - 3 Per Carton  
Barcode: 9311090003699