

## Premium Mineral 40-70 Extra Thick Oil (ET4070)

Nulon Premium Mineral 40-70 Extra Thick Engine Oil is a high viscosity, premium mineral engine oil formulated to provide the ultimate protection for engines used under severe conditions such as towing, racing or prolonged heavy use in hot climates.

Compared to lower viscosity oils, this high viscosity blend can reduce the signs of engine wear such as oil consumption, oil burning and blue/white exhaust smoke. This engine oil will also reduce the amount of oil loss past the piston rings making it suitable for old or worn engines.

### Benefits

- Extreme protection for 6 and 8 cylinder performance and competition engines
- Thicker viscosity keeps protecting even under heavy load
- Provides maximum performance and oil loss prevention for worn engines
- Maintains oil pressure and viscosity under severe conditions
- Enhanced protection for vehicles using E10, LPG and Methanol fuels
- Ensures maximum protection in race conditions
- Reduces oil burning and the need to top-up



### Typical Characteristics

SAE Viscosity Grade	25W-60
Viscosity @ 100°C (cSt) ASTM D445	26.95
Viscosity @ 40°C (cSt) ASTM D445	365.1
Viscosity Index ASTM D2270	99
Density @ 15°C (kg/L) ASTM D4052	0.8987
Sulphated Ash (mass %) ASTM D874	0.7
Total Base Number (mg KOH/g) ASTM D2896	5.7
Flash Point (°C) ASTM D92	239

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

### Warnings

NOTE: Not recommended for heavy-duty diesel engines. Refer to your vehicle service manual for correct lubricant requirements and service intervals.

CAUTION: Avoid skin contact with used oil. Wear suitable gloves. If skin contact occurs, wash immediately with soap and water. Avoid prolonged and repeated contact with used oil. Protect the environment. Do not pollute drains, ground or water with used oil.

Dispose of container as per EPA guidelines. Do not use this container for fuel or solvents.

### Meets or exceeds the following oil industry specifications

American Petroleum Institute	API SG, API CF
Blend Type	Mineral
Compatible Fuels	Light duty diesel, Methanol, Petrol
Viscosity	40-70

### Pack Sizes



Part No: ET40-70-5  
5 litres - 3 Per Carton  
Barcode: 9311090001060