

Premium Mineral 80W-90 Gearbox & Differential Oil

Nulon Premium Mineral 80W-90 Gearbox & Differential Oil is an extreme pressure API GL-5 limited slip and conventional hypoid differential oil, formulated for use in a wide range of Australian, American, Japanese, British and European passenger, 4x4, light commercial, trucks and construction equipment.

Suits: Ford, Holden, Mitsubishi, Nissan, Toyota and other manufacturers.

Benefits:

- Superior wear protection
- Reduces clutch chatter
- High thermal stability
- Advanced corrosion protection
- Suitable for use where an SAE90 fluid is specified



Safety

SAFETY DIRECTIONS: Avoid prolonged skin contact with used oil. During handling, wear suitable gloves and wash hands thoroughly after use.

FIRST AID: For advice, contact a Poisons Information Centre (Phone: Australia 131 126; New Zealand 0800 764 766) or a doctor (at once).

Meets or exceeds the following oil industry specifications	
American Petroleum Institute	API GL-5, API MT-1
BTR	BTR 5M-31
Ford	ESW-FM2C-1006A, ESW-FM2C-1006B, ESW-M2C-104A, ESW-M2C-105A, ESW-M2C-119A, SM-2C-1013A
GM Claims	HN 1187, HN 1386, HN 1561
Mack	Mack GO-J
Society of Automotive Engineers	SAE J2360
US Military	MIL-L-2105 B, MIL-L-2105 C, MIL-L-2105 D, MIL-PRF-2105E

Pack Sizes



Part No: LSD80W90-1E
1 Litre - 4 per carton
Barcode: 9311090005426



Part No: LSD80W90-20
20 litres - Single Unit
Barcode: 9311090005679