

Premium Mineral Automatic Transmission Fluid

Nulon Premium Mineral Automatic Transmission Fluid (NDEX3) is a mineral based Automatic Transmission Fluid (ATF) for use in many transmissions specifying General Motors Dexron® III and Ford Mercon® fluids. Nulon Premium Mineral Automatic Transmission Fluid provides excellent wear protection, smoother shifting and is suitable as a top up with other Dexron® and Mercon® fluids.

Benefits

- Excellent low temperature protection
- Compatible with wide range of seal materials
- Smooth transmission shift feel performance
- Excellent heat dissipation and foam suppression characteristics
- Can be used as top up with other Dexron® III and Mercon® fluids

Suitable for pre-2006 GM transmission that requires GM dexron® III and in many other transmissions that specify Dexron® or Mercon® transmission fluid requirements (except Ford Type F). For higher level performance and heavy duty protection, upgrade to Nulon Semi Synthetic Multi-Vehicle Automatic Transmission Fluid (NATF), or Nulon Full Synthetic Multi-Vehicle Automatic Transmission Fluid (SYNATF).



Application

- Automatic transmission that requires Dexron® III, Ford Mercon® and Allison C-4 performance
- Mitsubishi, Kia, and Hyundai automatic transmission SP-II/III
- Mazda transmission that requires Mazda III Fluid
- Toyota vehicles using 4 speed transmission (prior 2003)
- Suitable as a top up for automatic transmission and power steering system requiring Dexron® or Mercon® fluid

| Typical Characteristics | NDEX3 |
|-------------------------------------------------|--------|
| KV @ 100°C, mm ² /s, ASTM D445 | 7.520 |
| KV @ 40°C, mm ² /s, ASTM D445 | 40.28 |
| Viscosity Index, ASTM D2270 | 156 |
| Brookfield Viscosity @ -40°C, mPa.s, ASTM D2983 | 13000 |
| Flash point, °C, ASTM D92 | 208 |
| Density @ 15°C, g/mL, ASTM D4052 | 0.8540 |
| Pour Point, °C, ASTM D97 | -48 |

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

Health and Safety

Avoid prolonged skin contact with used oils. Wear suitable gloves. If skin contact occurs wash immediately with soap and water. Protect the environment. Do not pollute drains, ground or water with used oils. Dispose of container as per local EPA guidelines. Do not use this container for fuel or solvents.

| Meets or exceeds the following oil industry specifications | |
|------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|
| Allison | TES 389, C-4 |
| Caterpillar | T0-2 |
| Ford | M2C 138-CJ, M2C 166-H, Mercon® |
| GM Claims | Dexron®, Dexron® II, Dexron® IID, Dexron® IIE, Dexron® III, Dexron® IIIF, Dexron® IIIG, Dexron® IIIH, HN 2126 |
| Hyundai | SP-II, SP-III |
| Kia | SP-II, SP-III |
| Mazda | M-III |
| Mercedes Benz | MB 236.1, MB 236.5, MB 236.6, MB 236.7 |

Pack Sizes



Part No: NDEX3-1E
1 Litre - 4 per carton
Barcode: 9311090005525



Part No: NDEX3-4
4 Litres - 3 Per Carton
Barcode: 9311090004078



Part No: NDEX3-20
20 litres - Single Unit
Barcode: 9311090004085