

## Radiator & Cooling System Water (RCSW)

Ensures optimum coolant additive performance protection over the life of the coolant  
Guaranteed to provide cleaner and more efficient cooling over tap water

### Do it Once Do it Right

Radiator water contains fewer reactive chemicals resulting in optimum coolant life, system protection and anti-freeze and anti-boil performance.

All Nulon pre-mixed and top-up coolants use our premium deionised and demineralised Radiator & Cooling System Water.



### Directions for use

Fill your Radiator Cooling system with correct volume of Nulon Concentrated Coolant then top-up with Nulon Radiator & Cooling System Water.

### Why use

Why Nulon Radiator Water should always be used.

Probably the poorest choice of blending coolant is to use standard tap water. The minerals found in the water when introduced into engine coolant are the source of several concerns.

**Calcium:** forms scale on hot heat exchange surfaces with this radiator system. Scale is an insulator, and the result is localized engine overheating that can cause component failure.

**Magnesium:** also can form scale, creating localized overheating and heat damaged engine heads.

**Silicate:** In water, silicate is the result of sand, which is frequently found in cooling systems, and is associated with premature wear due to its natural abrasion.

**Chloride:** Most tap waters contain chlorine, resulting in the formation of chlorides in the coolant. Chlorides are aggressive to aluminium and can create premature wear.

**Oxygen:** Tap water is full of oxygen. Oxygen contributes to premature metal corrosion and rapid depletion of corrosion inhibitors thus reducing the effective life of the coolant.

### Pack Sizes



Part No: RCSW-5  
5 litres - 3 Per Carton  
Barcode: 9311090004719