

Red General Purpose Coolant Premix (GPPR)

Nulon Red General Purpose Coolant Premix is a ready to use, multi-purpose anti-freeze/anti-boil and corrosion inhibitor that is suitable for a wide variety of vehicles on Australian and New Zealand roads. This product is safe to use in a variety of vehicles as a top-up to existing anti-freeze and anti-boil red coolant or as a full service coolant for a full 4 years or 200,000km service life.

Benefits

- Anti-freeze and Anti-boil protection 4 years or 200,000km
- Contains long life inhibitor technology for corrosion protection of all cooling system metals
- Ready to use and suitable for a wide range of vehicles in Australia and New Zealand
- Protects aluminium, steel, cast iron, solder, copper and brass
- Provides maximum protection against cavitation damage and cylinder liner pitting
- Safe for all hoses, gaskets and seals



Directions for use

DIRECTIONS AS COMPLETE FILL: Refer to the owner's manual for cooling system capacity. If the system is clean, ensure the engine is switched off, turn the heater on and drain the old coolant (when cool) by removing the drain plug or bottom radiator hose. Then flush the cooling system with clean water to remove all traces of old coolant. Add Red General Purpose Coolant Premix. Secure the radiator cap start the engine, bleed air from the system if necessary. Check the coolant level is correct when the system is cool.

AS A TOP-UP TO EXISTING COOLANT: Add as top-up to existing red coolant, then start the engine and turn the heater on. When the engine is warm, turn it off and allow it to cool. Check the coolant level, and top it up if necessary. **NOTE:** The life of Red General Purpose Coolant Premix when used as a top-up, defaults to that of the original coolant in the cooling system. If you are unaware of the type or life of the coolant in the system we recommend a complete coolant change within the next 5000km or 6 months. For an OEM Replacement Coolant please use Nulon Long Life Coolant Part No. LL (green), RLL (red), or BLL (blue).

Typical Characteristics

GPPR	
Density (g/ml @ 15.6oC)	1.030 - 1.040
Freezing point	-8
Boiling point *	123
pH	8.0 - 9.0
Reserve alkalinity (ml)	2.8
Colour	Red
Glycol content (g/L)	196

* using 105kPa radiator cap

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

Safety Directions

SAFETY: May cause respiratory irritation. Use only outdoors or in a well-ventilated area. Store locked up.

FIRST AID: IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. Rinse mouth. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor (at once).

ENVIRONMENT: Do not pollute drains, soil or water with used products. After use, dispose of container in a responsible manner. Disposal of container should comply with local council regulations.

Meets or exceeds the following oil industry specifications	
AS Claims	AS 2108-2004 Type B
ASTM	ASTM D1384, ASTM D2570, ASTM D2809, ASTM D3306, ASTM D4340, ASTM D4985

Meets or exceeds the following oil industry specifications

Society of Automotive Engineers	SAE J1034, SAE J1941
---------------------------------	----------------------

Pack Sizes



Part No: GPPR-1
1 Litre - 6 Per Carton
Barcode: 9311090 004658



Part No: GPPR-4
4 Litres - 3 Per Carton
Barcode: 9311090 004641