

Semi Synthetic 15W-40 Modern Everyday Engine Oil

Nulon Semi Synthetic 15W-40 Modern Everyday Engine Oil is specifically formulated to provide outstanding anti-wear protection for modern petrol, light-duty diesel, motorcycle and LPG engines.

Nulon Semi Synthetic 15W-40 Modern Everyday Engine Oil meets the requirements of a vast array of vehicles, offering added protection and performance over conventional mineral engine oil. The formulation also provides excellent detergent and dispersant technology, reducing sludge and deposit formation.

Benefits

- Semi synthetic formula provides increased protection over mineral oils
- Provides maximum cold start protection
- Outstanding everyday protection during stop-start, city or highway driving
- High quality detergents and dispersants keep your engine clean
- High shear stable polymers giving excellent control of viscosity ensuring oil stays in spec for longer
- Suitable for use in motorcycles with and without a wet clutch

NOTE: Not recommended for heavy-duty diesel engines. Refer to your vehicle service manual for correct lubricant requirements and service intervals.



Typical Characteristics

SAE Viscosity Grade	15W-40
Viscosity @ 100°C (cSt) ASTM D445	14.99
Viscosity @ 40°C (cSt) ASTM D445	118.2
Apparent Viscosity by CCS @ -20°C (cP) ASTM D5293	6560
Apparent Viscosity by MRV @ -25°C (cP) ASTM D4684	25000
Viscosity Index ASTM D2270	131
Density @ 15°C (kg/L) ASTM D4052	0.8605
Sulphated Ash (mass %) ASTM D874	1.1
Total Base Number (mg KOH/g) ASTM D2896	11
Flash Point (°C) ASTM D92	230

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

Caution

CAUTION: Avoid skin contact with used oil. Wear suitable gloves. If skin contact occurs, wash immediately with soap and water. Avoid prolonged and repeated contact with used oil. Protect the environment. Do not pollute drains, ground or water with used oil. Dispose of container as per EPA guidelines. Do not use this container for fuel or solvents.

Meets or exceeds the following oil industry specifications

ACEA	ACEA A3/B3-12, ACEA A3/B4-12
American Petroleum Institute	API SN, API SM, API SH, API SL, API SJ, API SG
Blend Type	Semi Synthetic
Compatible Fuels	E85, Light duty diesel, LPG, Motorcycle, Petrol
JASO	JASO MA
Society of Automotive Engineers	SAE 15W-40
VW	VW 501.01, VW 505.00

Pack Sizes



Part No: ME15W40-5
5 litres - 3 Per Carton
Barcode: 9311090001091



Part No: ME15W40-1
1 Litre - 6 Per Carton
Barcode: 9311090000056



Part No: ME15W40-20
20 litres - Single Unit
Barcode: 9311090001251