

## Pro-Strength PTFE Dry Lube

Nulon Pro-Strength PTFE Dry Lube is formulated to lubricate, prevent sticking, stop squeaking and reduce friction and wear on most surfaces – including wood, metal, plastic, glass and rubber – without leaving undesirable oil residue. Nulon Pro-Strength PTFE Dry Lube is highly resistant to oil, acid, sand, dirt and built-up dust, offering high temperature protection up to 300°C.

### Recommended uses

Gears, locks, garage doors, leather, tracks, chains, gaskets, bearings, sleeves, drive trains, windows, drawers, roller drawer tracks, sliding glass doors, mirrors and more.

### Benefits

- Dry PTFE coating
- Extremely low coefficient of friction and high lubricity
- Non-sticky lubricant film
- Adhesion to a wide range of materials
- Prevents the accumulation of dust or dirt

Due to the chemical stability of PTFE, the film is resistant to attack by nitric acid, hydrochloric acid, sodium hydroxide and alcoholic potassium hydroxide in most applications. It is also extremely stable thermally (up to 300°C). Nulon PTFE Dry Lube is essentially insoluble in all non-fluorinated solvents.



### Directions For Use

#### Directions For Use:

Use at room temperature.

1. Shake can well before use.
2. Ensure the area to be treated is clean and dry.
3. Spray area to be lubricated directly and allow to dry.
4. Reapply as required.

Drying time of Nulon PTFE Dry Lube is dependent on the thickness of application.

### Caution

**Caution:** Keep away from heat/sparks/open flames/hot surfaces. Do not smoke when using product. Pressurised container: do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Avoid breathing spray. Wear protective gloves/eye protection. Use only outdoors or in a well-ventilated area.

### Pack Sizes



Part No: PDL300  
300 ml - 6 Per Carton  
Barcode: 9311090005235