

Premium Mineral Automatic Transmission Fluid

Nulon Premium Mineral Automatic Transmission Fluid (NDEX3) is a mineral based Automatic Transmission Fluid (ATF) for use in many transmissions specifying General Motors Dexron® III and Ford Mercon® fluids. Nulon Premium Mineral Automatic Transmission Fluid provides excellent wear protection, smoother shifting and is suitable as a top up with other Dexron® and Mercon® fluids.

Benefits

- Excellent low temperature protection
- Compatible with wide range of seal materials
- Smooth transmission shift feel performance
- Excellent heat dissipation and foam suppression characteristics
- Can be used as top up with other Dexron® III and Mercon® fluids

Suitable for pre-2006 GM transmission that requires GM dexron® III and in many other transmissions that specify Dexron® or Mercon® transmission fluid requirements (except Ford Type F). For higher level performance and heavy duty protection, upgrade to Nulon Semi Synthetic Multi-Vehicle Automatic Transmission Fluid (NATF), or Nulon Full Synthetic Multi-Vehicle Automatic Transmission Fluid (SYNATF).



Application

- Automatic transmission that requires Dexron® III, Ford Mercon® and Allison C-4 performance
- Mitsubishi, Kia, and Hyundai automatic transmission SP-II/III
- Mazda transmission that requires Mazda III Fluid
- Toyota vehicles using 4 speed transmission (prior 2003)
- Suitable as a top up for automatic transmission and power steering system requiring Dexron® or Mercon® fluid

Typical Characteristics	NDEX3
KV @ 100°C, mm ² /s, ASTM D445	7.520
KV @ 40°C, mm ² /s, ASTM D445	40.28
Viscosity Index, ASTM D2270	156
Brookfield Viscosity @ -40°C, mPa.s, ASTM D2983	13000
Flash point, °C, ASTM D92	208
Density @ 15°C, g/mL, ASTM D4052	0.8540
Pour Point, °C, ASTM D97	-48

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

Health and Safety

Avoid prolonged skin contact with used oils. Wear suitable gloves. If skin contact occurs wash immediately with soap and water. Protect the environment. Do not pollute drains, ground or water with used oils. Dispose of container as per local EPA guidelines. Do not use this container for fuel or solvents.

Meets or exceeds the following oil industry specifications	
Allison	TES 389, C-4
Caterpillar	T0-2
Ford	M2C 138-CJ, M2C 166-H, Mercon®
GM Claims	Dexron®, Dexron® II, Dexron® IID, Dexron® IIE, Dexron® IIIF, Dexron® IIIG, Dexron® IIIH, HN 2126
Hyundai	SP-II, SP-III
Kia	SP-II, SP-III
Mazda	M-III
Mercedes Benz	MB 236.1, MB 236.5, MB 236.6, MB 236.7

Pack Sizes



Part No: NDEX3-4
4 Litres - 3 Per Carton
Barcode: 9311090004078



Part No: NDEX3-1
1 Litre - 6 Per Carton
Barcode: 9311090004061



Part No: NDEX3-20
20 litres - Single Unit
Barcode: 9311090004085