

Full Synthetic 5W-20 Fuel Conserving Engine Oil

Nulon Full Synthetic 5W-20 Fuel Conserving Engine Oil is designed to provide the ultimate protection for all new-generation passenger car and light commercial petrol engines that require an ultra-low viscosity 5W-20 engine oil. Specifically formulated to provide optimum fuel economy while maintaining a high level of engine protection during long oil drain intervals and cold start-up.

Recommended for use in both turbocharged and non-turbocharged petrol engines.

Meets ILSAC GF-5 energy conserving requirements and delivers greater fuel economy and engine protection. Additional anti-wear additives provide maximum performance and protection to engine and turbocharger components, while enhanced corrosion protection provides bio-fuel compatibility for vehicles using E10 and E85 fuels.

Nulon Full Synthetic 5W-20 Fuel Conserving Engine Oil has added Molybdenum Dithiocarbamate to give you additional high-level wear protection and performance. Molybdenum Dithiocarbamate is proven to dramatically reduce friction and provide increased engine wear protection from cold start to extreme temperatures, giving you added benefits over standard engine oil alone.

Benefits

- Ultra low viscosity fuel efficient formula
- Added Molybdenum Dithiocarbamate provides more protection and performance over engine oil alone
- Provides excellent cold startup protection
- Ultrafast flowing formula
- Provides excellent engine cleanliness
- Provides excellent oxidation control and thermal stability
- Oil stays in-spec during long drain intervals

NOTE: Not recommended for heavy-duty diesel engines. Refer to your vehicle service manual for correct lubricant requirements and service intervals.



Typical Characteristics

SAE Viscosity Grade	5W-20
Viscosity @ 100°C (cSt) ASTM D445	8.860
Viscosity @ 40°C (cSt) ASTM D445	53.47
Apparent Viscosity by CCS @ -30°C (cP) ASTM 5293	6040
Apparent Viscosity by MRV @ -35°C (cP) ASTM 4684	19400
Viscosity Index ASTM D2270	145
Density @ 15°C (kg/L) ASTM D4052	0.8542
Sulphated Ash (mass %) ASTM D874	0.9
Total Base Number (mg KOH/g) ASTM D2896	7.5
Flash Point (°C) ASTM D92	225

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

Caution

CAUTION: Avoid skin contact with used oil. Wear suitable gloves. If skin contact occurs, wash immediately with soap and water. Avoid prolonged and repeated contact with used oil. Protect the environment. Do not pollute drains, ground or water with used oil. Dispose of container as per EPA guidelines. Do not use this container for fuel or solvents.

Meets or exceeds the following oil industry specifications	
American Petroleum Institute	API SN, API SM, API SL, API SJ, API SG
Blend Type	Full Synthetic
Compatible Fuels	E85, LPG, Petrol
Ford	Ford WSS M2C 945A
ILSAC	ILSAC GF-5
Moly DTC	Contains Moly DTc
Society of Automotive Engineers	SAE 5W-20

Suitable for use in the following manufacturers

Chrysler
Dodge
Ford
Honda

Hyundai
Jaguar
Kia
Land Rover
Lexus
Mazda
Subaru
Suzuki
Toyota

Pack Sizes



Part No: SYN5W20-5
5 litres - 3 Per Carton
Barcode: 9311090003842



Part No: SYN5W20-1
1 Litre - 6 Per Carton
Barcode: 9311090003835