

## Full Synthetic 5W-30 Ford, Hyundai, Kia, Mazda Specification Engine Oil

Nulon Full Synthetic 5W-30 Fuel Efficient Engine Oil provides the maximum protection and performance from cold start-up to high operating temperatures. The fuel conserving, low viscosity formula ensures optimum engine performance for all technically advanced and performance petrol, passenger and light commercial diesel engines

Nulon Full Synthetic 5W-30 Fuel Efficient Engine Oil is specifically designed for fuel efficiency with improved wear protection and sludge handling.

### Benefits

- Provides maximum cold-start protection
- Added Moly DTC provides additional protection over standard engine oil alone
- Outstanding wear protection during stop-start, city or highway driving
- Energy and fuel conserving formula
- High-quality detergents and dispersants reduce internal engine deposits
- High shear stable polymers ensure oil stays in spec for longer



### Typical Characteristics

SAE Viscosity Grade	5W-30
Viscosity @ 100°C (cSt) ASTM D445	10.45
Viscosity @ 40°C (cSt) ASTM D445	63.31
Apparent Viscosity by CCS @ -30°C (cP) ASTM D5293	5940
Apparent Viscosity by MRV @ -35°C (cP) ASTM D4684	29000
Viscosity Index ASTM D2270	154
Density @ 15°C (kg/L) ASTM D4052	0.8554
Sulphated Ash (mass %) ASTM D874	0.9
Total Base Number (mg KOH/g) ASTM D2896	7.9
Flash Point (°C) ASTM D92	223

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

### Caution

**Note:** Not recommended for diesel engines with [Diesel Particulate Filters \(DPF\)](#) or for heavy-duty diesel engines. Refer to your vehicle service manual for correct lubrication requirements and service intervals.

**CAUTION:** Avoid skin contact with used oil. Wear suitable gloves. If skin contact occurs, wash immediately with soap and water. Avoid prolonged and repeated contact with used oil. Protect the environment. Do not pollute drains, ground or water with used oil. Dispose of container as per EPA guidelines. Do not use this container for fuel or solvents.

Meets or exceeds the following oil industry specifications	
ACEA	ACEA A5/B5-10
American Petroleum Institute	API SL, API CF
Compatible Fuels	Light duty diesel, Petrol
Ford	Ford WSS-M2C913-A, Ford WSS-M2C913-B, Ford WSS-M2C913-C, Ford WSS-M2C913-D
Moly DTC	Contains Moly DTC
Renault	Renault RN0700
Society of Automotive Engineers	SAE 5W-30

### Pack Sizes



Part No: SYNFE5W30-5  
5 litres - 3 Per Carton  
Barcode: 9311090004511



Part No: SYNFE5W30-1  
1 Litre - 6 Per Carton  
Barcode: 9311090004504



Part No: SYNFE5W30-10  
10 litres - Single Unit  
Barcode: 9311090005174