

Full Synthetic 5W-40 Long Life Performance Engine Oil

Nulon Full Synthetic 5W-40 Long Life Performance Engine Oil is designed to provide the ultimate protection for all technically advanced passenger cars and light commercial petrol and diesel engines that require a 5W-40 viscosity engine oil. Specifically formulated to provide increased protection during long oil drain intervals. Recommended for use in both turbocharged and non-turbocharged petrol and diesel* engines.

*For vehicles requiring DPF safe oil please use [Nulon Full Synthetic Passenger and Light Commercial Diesel Engine Oil \(SYND5W40\)](#)

Nulon Full Synthetic 5W-40 Long Life Performance Engine Oil has added Molybdenum Dithiocarbamate (Moly DTC) to give you additional peace of mind performance. Moly DTC is proven to dramatically reduce friction and provide increased engine wear protection from cold start to extreme temperatures, giving you additional benefits over standard engine oil additives alone. For further information go to www.lessfriction.com.au

Benefits

- Increased protection for harder driven and high-performance engines.
- Fast flowing formula provides excellent cold start-up protection
- Added Moly DTC provides additional protection over standard engine oil alone.
- Provides excellent engine cleanliness
- Provides excellent oxidation control and thermal stability
- Oil stays in-spec during long drain intervals

NOTE Not recommended for heavy-duty diesel engines or vehicles fitted with DPF. Refer to your vehicle service manual for correct lubricant requirements and service intervals.



Typical Characteristics

SAE Viscosity Grade	5W-40
Viscosity @ 100°C (cSt) ASTM D445	13.33
Viscosity @ 40°C (cSt) ASTM D445	82.21
Apparent Viscosity by CCS @ -30°C (cP) ASTM D5293	5610
Apparent Viscosity by MRV @ -35°C (cP) ASTM D4684	24700
Viscosity Index ASTM D2270	164
Density @ 15°C (kg/L) ASTM D4052	0.8561
Sulphated Ash (mass %) ASTM D874	1.2
Total Base Number (mg KOH/g) ASTM D2896	9.9
Flash Point (°C) ASTM D92	222

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

Caution

CAUTION Avoid skin contact with used oil. Wear suitable gloves. If skin contact occurs, wash immediately with soap and water. Avoid prolonged and repeated contact with used oil. Protect the environment. Do not pollute drains, ground or water with used oil. Dispose of container as per EPA guidelines. Do not use this container for fuel or solvents.

Meets or exceeds the following oil industry specifications

ACEA	ACEA A3/B3, ACEA A3/B3-12, ACEA A3/B4, ACEA A3/B4-12
American Petroleum Institute	API SN, API SM, API SL, API SJ, API SG, API CF
Blend Type	Full Synthetic
BMW	BMW LL-01
Compatible Fuels	E85, Light duty diesel, Petrol
Ford	Ford WSS M2C 945A
GM	GM-LL-025
Mercedes Benz	MB 229.3, MB 229.5
Moly DTC	Contains Moly DTC
Other Claims	MTU Oil Category 2
Peugeot	PSA B71 2296

Meets or exceeds the following oil industry specifications

Porsche	Porsche A40
Renault	Renault RN0700, Renault RN0710
Society of Automotive Engineers	SAE 5W-40
VW	VW 502.00, VW 505.00

Suitable for use in the following manufacturers

Audi
Bentley
Chrysler
Ferrari
Ford
Hyundai
Jaguar
Kia
Land Rover
Lexus
Lotus
Mitsubishi
Nissan
Peugeot
Porsche
Saab
Ssangyong
Volvo

Pack Sizes



Part No: SYN5W40-5
5 litres - 3 Per Carton
Barcode: 9311090000018



Part No: SYN5W40-1
1 Litre - 6 Per Carton
Barcode: 9311090002739



Part No: SYN5W40-10
10 litres - Single Unit
Barcode: 9311090002746

NULON



Part No: SYN5W40-20
20 litres - Single Unit
Barcode: 9311090001213