

Pro-Strength Premium Mineral 15W-40 Everyday Engine Oil

Nulon Pro-Strength Premium Mineral 15W-40 Everyday Engine Oil is formulated with virgin mineral base oils and high-performance additives which provide optimum performance and protection to most late model engines.

Nulon Premium Mineral 15W-40 Everyday Engine Oil promotes easier cold starting, reduces wear and keeps the engine clean between the recommended oil drain intervals.

For increased performance and protection use Nulon Semi Synthetic 15W-40 Modern Everyday Engine Oil (Part No. ME15W40).

Benefits

- Maintains viscosity at high temperature
- Anti-wear protection to extend the life of the engine
- Enhanced detergency to clean and prevent sludge formation
- Contains anti-oxidants to prolong the life of the oil between drain intervals
- Faster oil flow improves cold starting
- Safe for catalytic converters
- Suitable as a running-in oil



Typical Characteristics

SAE Viscosity Grade	15W-40
Viscosity @ 100°C (cSt) ASTM D445	15.09
Viscosity @ 40°C (cSt) ASTM D445	121.6
Apparent Viscosity by CCS @ -20°C (cP) ASTM D5293	5950
Apparent Viscosity by MRV @ -25°C (cP) ASTM D4684	24700
Viscosity Index ASTM D2270	128
Density @ 15°C (kg/L) ASTM D4052	0.8753
Sulphated Ash (mass %) ASTM D874	0.8
Total Base Number (mg KOH/g) ASTM D2896	6
Flash Point (°C) ASTM D92	227

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

Warnings

NOTE: Not recommended for heavy-duty diesel engines. Refer to your vehicle service manual for correct lubricant requirements and service intervals.

CAUTION: Avoid skin contact with used oil. Wear suitable gloves. If skin contact occurs, wash immediately with soap and water. Avoid prolonged and repeated contact with used oil. Protect the environment. Do not pollute drains, ground or water with used oil. Dispose of container as per EPA guidelines. Do not use this container for fuel or solvents.

Meets or exceeds the following oil industry specifications

American Petroleum Institute	API SL, API SJ, API CF
Blend Type	Mineral
Compatible Fuels	Light duty diesel, Petrol
Society of Automotive Engineers	SAE 15W-40

Pack Sizes



Part No: PM15W40-205
205 Litre Drum - Single Unit
Barcode: