

Pro-Strength Semi-Synthetic 10W-30 Hi-Tech Fast-Flowing Engine Oil

Nulon Pro-Strength Semi-Synthetic 10W-30 Hi-Tech Fast-Flowing Engine Oil's low viscosity formulation provides excellent anti-wear protection from the moment you start the engine. Formulated for high-performance multi-valve and turbocharged 4, 6 and 8 cylinder modern petrol engines including LPG. Suitable for light duty diesel engines.

Benefits

- Superior semi-synthetic formula provides enhanced protection over mineral oils
- Suits modern Australian, Japanese, US and European vehicles
- Provides excellent fuel economy over thicker mineral oils
- Provides maximum cold start engine protection
- Enhanced protection for vehicles using E10, E85 and LPG fuels
- Reduced oil consumption compared to mineral-based fluids
- Excellent detergent and dispersant technology to keep engines clean and protected from deposits
- High shear stable polymers provide optimum control of viscosity
- Safe for catalytic converters

NOTE: Not recommended for heavy-duty diesel engines. Refer to your vehicle service manual for correct lubricant requirements and service intervals.



Typical Characteristics

SAE Viscosity Grade	10W-30
Viscosity @ 100°C (cSt) ASTM D445	11.51
Viscosity @ 40°C (cSt) ASTM D445	78.55
Apparent Viscosity by CCS @ -25°C (cP) ASTM D5293	6260
Apparent Viscosity by MRV @ -30°C (cP) ASTM D4684	23400
Viscosity Index ASTM D2270	139
Density @ 15°C (kg/L) ASTM D4052	0.8674
Sulphated Ash (mass %) ASTM D874	0.8
Total Base Number (mg KOH/g) ASTM D2896	6.9
Flash Point (°C) ASTM D92	222

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

Caution

CAUTION: Avoid skin contact with used oil. Wear suitable gloves. If skin contact occurs, wash immediately with soap and water. Avoid prolonged and repeated contact with used oil. Protect the environment. Do not pollute drains, ground or water with used oil. Dispose of container as per EPA guidelines. Do not use this container for fuel or solvents.

Meets or exceeds the following oil industry specifications	
American Petroleum Institute	API SN, API SM, API SH, API SL, API SJ, API SG
Blend Type	Semi Synthetic
Compatible Fuels	E85, LPG, Petrol
ILSAC	ILSAC GF-5
Society of Automotive Engineers	SAE 10W-30

Pack Sizes



Part No: HT10W30-205
205 Litre Drum - Single Unit
Barcode: