

Semi Synthetic 10W-40 High Performance Engine Oil

Semi synthetic formula designed for Australian, Japanese, US and European high performance non-turbocharged and turbocharged petrol engines. The semi synthetic formula provides excellent anti-wear protection while offering excellent fuel economy.

The advanced formulation will keep your engine cool and clean during city or highway driving and prevent sludge build-up over time.

For increased protection and performance choose Nulon Full Synthetic 10W-40 Hi Tech Engine Oil (Part No. SYN10W40).

Benefits

- High-performance semi synthetic oil for modern vehicles and motorcycles.
- Provides excellent high-temperature protection for city and highway driving.
- Suitable for a wide range of vehicles and operating conditions.
- Improved oil film strength helps to reduce metal to metal contact
- Suitable for vehicles using E10, E85, light-duty diesel, and LPG fuels
- Formulated to keep your engine cool and clean
- Excellent low temperature, cold start performance
- Extremely effective anti-oxidant agent to prevent sludge formation
- Suitable for motorcycle with and without a wet clutch

NOTE: Not recommended for heavy-duty diesel engines. Refer to your vehicle service manual for correct lubricant requirements and service intervals.



Typical Characteristics

SAE Viscosity Grade	10W-40
Viscosity @ 100°C (cSt) ASTM D445	15.08
Viscosity @ 40°C (cSt) ASTM D445	106.6
Apparent Viscosity by CCS @ -25°C (cP) ASTM D5293	6141
Apparent Viscosity by MRV @ -30°C (cP) ASTM D4684	29400
Viscosity Index ASTM D2270	148
Density @ 15°C (kg/L) ASTM D4052	0.8687
Sulphated Ash (mass %) ASTM D874	1.1
Total Base Number (mg KOH/g) ASTM D2896	11
Flash Point (°C) ASTM D92	216

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

Caution

CAUTION: Avoid skin contact with used oil. Wear suitable gloves. If skin contact occurs, wash immediately with soap and water. Avoid prolonged and repeated contact with used oil. Protect the environment. Do not pollute drains, ground or water with used oil. Dispose of container as per EPA guidelines. Do not use this container for fuel or solvents.

Meets or exceeds the following oil industry specifications	
ACEA	ACEA A3/B3-12, ACEA A3/B4-12
American Petroleum Institute	API SN, API SM, API SH, API SL, API SJ, API SG
Blend Type	Semi Synthetic
Compatible Fuels	E85, Light duty diesel, LPG, Motorcycle, Petrol
JASO	JASO MA
Mercedes Benz	MB 229.1, MB 229.3
Peugeot	PSA B71 2300
Renault	Renault RN0710
Society of Automotive Engineers	SAE 10W-40
VW	VW 502.00, VW 505.00

Pack Sizes



Part No: SEM10W40-5
5 litres - 3 Per Carton
Barcode: 9311090003804



Part No: SEM10W40-1
1 Litre - 6 Per Carton
Barcode: 9311090003798