

Semi Synthetic 5W-30 Advanced Protection Engine Oil

Nulon Semi Synthetic 5W-30 Advanced Protection Engine Oil provides advanced protection for modern petrol passenger cars that require a low viscosity 5W-30 engine oil. The technically advanced semi synthetic formula provides additional protection and performance over standard mineral engine oil. Specifically formulated to provide protection during long oil drain intervals and ensure the engine is protected on cold start-up.

High-temperature stability provides increased oxidation control in both turbocharged and non-turbocharged petrol engines.

For increased protection and performance choose Nulon Full Synthetic 5W-30 Long Life Engine Oil (Part No. SYN5W30).

Benefits

- Advanced semi synthetic formulation for modern passenger cars
- Low viscosity formula provides excellent fuel economy
- Fast flow formula provides instant cold start protection
- Enhanced protection for vehicles using E10, E85 and LPG fuels
- Premium detergents ensure excellent engine cleanliness
- High temperature stability provides excellent oxidation control
- Oil stays in-spec during long drain intervals

NOTE: Not recommended for heavy-duty diesel engines or vehicles fitted with DPF. Refer to your vehicle service manual for correct lubricant requirements and service intervals.



Typical Characteristics

SAE Viscosity Grade	5W-30
Viscosity @ 100°C (cSt) ASTM D445	11.47
Viscosity @ 40°C (cSt) ASTM D445	71.02
Apparent Viscosity by CCS @ -30°C (cP) ASTM D5293	6040
Apparent Viscosity by MRV @ -35°C (cP) ASTM D4684	27700
Viscosity Index ASTM D2270	155
Density @ 15°C (kg/L) ASTM D4052	0.8576
Sulphated Ash (mass %) ASTM D874	0.8
Total Base Number (mg KOH/g) ASTM D2896	8.1
Flash Point (°C) ASTM D92	220

Due to continued product research and development the information contained in this Product Bulletin is subject to change without notification.

Caution

CAUTION: Avoid skin contact with used oil. Wear suitable gloves. If skin contact occurs, wash immediately with soap and water. Avoid prolonged and repeated contact with used oil. Protect the environment. Do not pollute drains, ground or water with used oil.

Dispose of container as per EPA guidelines. Do not use this container for fuel or solvents.

Meets or exceeds the following oil industry specifications	
American Petroleum Institute	API SN, API SM, API SH, API SL, API SJ, API SG
Blend Type	Semi Synthetic
Compatible Fuels	E85, LPG, Petrol
Ford	Ford WSS M2C 945A, Ford WSS M2C 946A
ILSAC	ILSAC GF-5
Society of Automotive Engineers	SAE 5W-30

Suitable for use in the following manufacturers

Audi
Chrysler
Ford
Holden
Honda
Hyundai
Jaguar
Kia
Land Rover

Lexus
Mazda
Mitsubishi
Nissan
Peugeot
Renault
Saab
Subaru
Toyota
Volvo

Pack Sizes



Part No: SEM5W30-5
5 litres - 3 Per Carton
Barcode: 9311090003781



Part No: SEM5W30-1
1 Litre - 6 Per Carton
Barcode: 9311090003774